

Product Code: FPBS038BK

Luckinslive 389089030

Description: 5A Round Pin Socket Outlet



General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 1.3 (D)	
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 3 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Flat Plate	
Finish	Brushed Stainless	
Insert Colour	Black	
Gasket Colour	Transparent (Neoprene)	
Materials	Front Plate: Stainless Steel	Insert: Urea
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	5	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	4 x 1.5 or 3 x 2.5	
Switched	No	
Twin Earth Terminals	No	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

