

Product Code: FPBS421

Luckinslive 389089755

Description: 10AX 1 Gang 2 Way Toggle Plate Switch



General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 1.3 (D)	
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 3 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Flat Plate	
Finish	Brushed Stainless	
Gasket Colour	Transparent (Neoprene)	
Switch Finish	Pearl Nickel	
Materials	Front Plate: Stainless Steel	Switch Front & Nut: Cast Zinc
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	4.9 x 4.1	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125PN for pearl nickel finish.

