


Product Code: VPCH424

Luckinslive 389112185

Description: 10AX 4 Gang 2 Way Toggle Plate Switch



## General Information

|                                        |                                             |                                          |
|----------------------------------------|---------------------------------------------|------------------------------------------|
| Plate Dimensions (mm)                  | 146 (W) x 88 (H) x 8 (D)                    |                                          |
| Dimensions With Gasket (mm)            | 149 (W) x 91 (H) x 9 (D)                    |                                          |
| Plate Fixing Centres - Horizontal (mm) | 120.6                                       |                                          |
| Style                                  | Victorian                                   |                                          |
| Finish                                 | Polished Chrome                             |                                          |
| Gasket Colour                          | Supplied With Both Black & White Gasket     |                                          |
| Switch Finish                          | Polished Chrome                             |                                          |
| Materials                              | Front Plate: Stainless Steel                | Switch Front & Nut: Cast Zinc            |
|                                        | Rear Housing: Nylon                         | Terminals: Brass                         |
|                                        | Terminal Screws: Steel & Yellow Passivated  | Contacts: Silver "on-lay" Copper / Brass |
|                                        | Internal Busbars: Formed Pressed Brass      | Earth Strap: Mild Steel                  |
|                                        | Gasket: Nylon                               |                                          |
| Anti Microbial Certified               | No                                          |                                          |
| Operating Voltage (AC)                 | 250                                         | Frequency (Hz) 50                        |
| Inductive Load Rating (AX)             | 10                                          |                                          |
| Load Rating Comments                   | Suitable for Fluorescent or Inductive Loads |                                          |
| Termination Type                       | Screw                                       |                                          |
| Terminal Size (mm)                     | 4.9 x 4.1                                   | Terminal Torque Value (Nm) 1.2           |
| Terminal Capacity - Solid (mm²)        | 4 x 1.5 or 2 x 2.5                          |                                          |
| Modular Rocker Switches                | Yes                                         |                                          |
| 2 Way Switch                           | Yes                                         |                                          |
| Minimum Back Box Depth (mm)            | 25                                          |                                          |
| Ingress Protection                     | IP20                                        |                                          |
| Operational Temperature (°C)           | -5 to +40                                   |                                          |
| Warranty (Years)                       | 20                                          |                                          |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125CH for polished chrome finish.

