

Product Code: VPSS411WH
Description: 10AX Ingot 1 Gang 2 Way Plate Switch

Luckinslive 389117355



General Information

Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)		
Dimensions With Gasket (mm)	g1 (W) x g1 (H) x g (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
MiniGrid Plate (Gang)	1		
MiniGrid Single Width Module Quantity	1		
MiniGrid Double Width Module Quantity	0		
Style	Victorian		
Finish	Stainless Steel		
Insert Colour	White		
Gasket Colour	White		
Materials	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel		
Anti Microbial Certified	No		
Operating Voltage (AC)	250		
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5		
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5		
Modular Rocker Switches	Yes		
2 Way Switch	Yes		
Minimum Back Box Depth (mm)	16		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		
	Insert: Urea	Frequency (Hz)	50
	Rear Housing: Nylon		
	Terminal Screws: Steel & Yellow Passivated		
	Internal Busbars: Formed Pressed Brass		
	Gasket: Nylon		
	Terminal Torque Value (Nm)	0.5	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.

